



中国认可
检测
TESTING
CNAS L0748



NO.1116100181

检 测 报 告

Test Report

样品名称： 锂离子电池组 SBC-B09 36V 604Wh

Name of Sample: /

委托单位： 太普电子（常熟）有限公司

Consignor: /



上海化工研究院检测中心

Shanghai Research Institute of Chemical Industry Testing Centre


上海化工研究院检测中心
检验报告


SRICI Testing Centre Test Report


NO. 1116100181


1/11

样品名称 Name of Sample	中文 Chinese	锂离子电池组 SBC-B09 36V 604Wh	
	英文 English	/	
样品编号 Sample No.	1116100181		
委托单位 Consignor	太普电子(常熟)有限公司 /		
生产单位 Manufacturer	太普电子(常熟)有限公司 /		
检验方法 Test method	联合国《关于危险货物运输的建议书 试验和标准手册》 ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 UNITED NATIONS "Recommendations on the TRANSPORT OF DANGEROUS GOODS" Manual of Tests and Criteria ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3		
判定标准 Criterion	联合国《关于危险货物运输的建议书 试验和标准手册》 ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 UNITED NATIONS "Recommendations on the TRANSPORT OF DANGEROUS GOODS" Manual of Tests and Criteria ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3		
样品外观 Appearance	黑色塑胶外壳 Black Plastics cement shell		
样品接受日期 Accepted Date	2016-10-27	检测起迄日期 Test Date	2016-10-29 ~ 2017-01-16
检测项目 Test Items	高度模拟;热测试;振动;冲击;外短路;撞击;过充电;强制放电 Altitude simulation, Thermal test, Vibration, Shock, External short circuit, Impact, Overcharge, Forced discharge		
检验结论 Conclusion	经检验,该样品符合联合国《关于危险货物运输的建议书 试验和标准手册》 ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3标准要求。 The sample has passed the test items of UNITED NATIONS "Recommendations on the TRANSPORT OF DANGEROUS GOODS" Manual of Tests and Criteria ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3.		
备注 Comment	可充电锂电池组 Rechargeable Lithium Battery. 生效日期(Date): 2017-01-17		
委托单位地址 Consignor Address	/		邮政编码 Post Code 215500



批准
Approver: 
职务
Title: 副总工程师(Vice chief engineer)

审核
Checker: 

编制
Compiler: 



上海化工研究院检测中心 检验报告

SRICI Testing Centre Test Report

NO. 1116100181

2/11

序号 No.	检验项目名称 Name of Test Items	标准要求或标准条款号 Standard requirement or The Clause Number of Standard	检测结果 Test Result	本项结论 Conclusion	备注 Remark	
1	高度模拟 Altitude simulation	联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC.10/11/Rev.5/Amend.1 38.3 试验 T.1 UN Manual of Tests and Criteria Section ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 Test T.1	见附表 1 See Appendix 1	合格 Passed	/	
2	热测试 Thermal test	联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC.10/11/Rev.5/Amend.1 38.3 试验 T.2 UN Manual of Tests and Criteria Section ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 Test T.2	见附表 2 See Appendix 2	合格 Passed	/	
3	振动 Vibration	联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC.10/11/Rev.5/Amend.1 38.3 试验 T.3 UN Manual of Tests and Criteria Section ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 Test T.3	见附表 3 See Appendix 3	合格 Passed	/	
4	冲击 Shock	联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC.10/11/Rev.5/Amend.1 38.3 试验 T.4 UN Manual of Tests and Criteria Section ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 Test T.4	见附表 4 See Appendix 4	合格 Passed	/	
5	外短路 External short circuit	联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC.10/11/Rev.5/Amend.1 38.3 试验 T.5 UN Manual of Tests and Criteria Section ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 Test T.5	见附表 5 See Appendix 5	合格 Passed	/	
6	撞击 Impact	联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 试验 T.6 UN Manual of Tests and Criteria Section ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 Test T.6	见附表 6 See Appendix 6	合格 Passed	/	
7	过充电 Overcharge	联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 试验 T.7 UN Manual of Tests and Criteria Section ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 Test T.7	见附表 7 See Appendix 7	合格 Passed	/	
8	强制放电 Forced discharge	联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC.10/11/Rev.5/Amend.1 38.3 试验 T.8 UN Manual of Tests and Criteria Section ST/SG/AC.10/11/Rev.5/Amend.1&Amend.2 38.3 Test T.8	见附表 8 See Appendix 8	合格 Passed	/	
检验环境条件 Test Environment Condition		环境温度:17℃-23℃;环境湿度:/% Ambient temperature:17℃-23℃;Ambient humidity:/%				
分包检验情况 Subcontracted Test Condition		检验项目 Test Item	/			
		分包实验室 Subcontracted Laboratory	名称 Name	/	邮编 Post Code	/
			地址 Address	/	电话 Tel	/

上海化工研究院检测中心
检验报告-附表 8

SRICI Testing Centre Test Report—Appendix 8 NO. 1116100181

10/11

序号 No.	8	检验项目名称 Name of Test Items	强制放电 Forced discharge
样品编号 Sample No.	样品状态 Sample Status	其他现象 Other Event	
022	1CYC完全放电 1CYC Fully discharged		O
023	1CYC完全放电 1CYC Fully discharged		O
024	1CYC完全放电 1CYC Fully discharged		O
025	1CYC完全放电 1CYC Fully discharged		O
026	1CYC完全放电 1CYC Fully discharged		O
027	1CYC完全放电 1CYC Fully discharged		O
028	1CYC完全放电 1CYC Fully discharged		O
029	1CYC完全放电 1CYC Fully discharged		O
030	1CYC完全放电 1CYC Fully discharged		O
031	1CYC完全放电 1CYC Fully discharged		O
032	50CYC完全放电 50CYC Fully discharged		O
033	50CYC完全放电 50CYC Fully discharged		O
034	50CYC完全放电 50CYC Fully discharged		O
035	50CYC完全放电 50CYC Fully discharged		O
036	50CYC完全放电 50CYC Fully discharged		O
037	50CYC完全放电 50CYC Fully discharged		O
038	50CYC完全放电 50CYC Fully discharged		O
039	50CYC完全放电 50CYC Fully discharged		O
040	50CYC完全放电 50CYC Fully discharged		O
041	50CYC完全放电 50CYC Fully discharged		O
备注: D-解体 F-起火 O-无解体、无起火。 Note: D-Disassembly F-Fire O-No Disassembly & No Fire.			

上海化工研究院检测中心
检验报告-附图

SRICI Testing Centre Test Report—Appendix

NO. 1116100181


11/11

TEMPERATURE RANGE

 <95°F <35°C	 32°F / 0°C 122°F / 50°C	 -4°F / 20°C 158°F / 70°C
Storage	Charge	Ride

RECYCLE CE

SPECIALIZED BICYCLE COMPONENTS INC.
Rechargeable Li-Ion Battery
This battery must be disposed of properly
SBC-B09-16.8Ah/604Wh / 36V 101NR21/71-4
Made in P.R.C



报告结束